

(12) **United States Patent**
Lee

(10) **Patent No.:** **US 9,636,754 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **REAMER**

(71) Applicant: **MEENG GANE ENTERPRISE CO., LTD.**, Taichung (TW)

(72) Inventor: **Yu-Jyun Lee**, Taichung (TW)

(73) Assignee: **MEENG GANE ENTERPRISE CO., LTD.**, Taichung (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 92 days.

(21) Appl. No.: **14/539,211**

(22) Filed: **Nov. 12, 2014**

(65) **Prior Publication Data**

US 2015/0298218 A1 Oct. 22, 2015

(30) **Foreign Application Priority Data**

Apr. 18, 2014 (TW) 103206748 U

(51) **Int. Cl.**

B23B 51/00 (2006.01)

B23D 77/12 (2006.01)

B23B 51/10 (2006.01)

(52) **U.S. Cl.**

CPC **B23B 51/0018** (2013.01); **B23B 51/107** (2013.01); **B23D 77/12** (2013.01); **B23B 2251/02** (2013.01); **B23B 2260/0482** (2013.01); **B23D 2277/02** (2013.01); **Y10T 279/17846** (2015.01); **Y10T 279/17957** (2015.01); **Y10T 408/8925** (2015.01); **Y10T 408/906** (2015.01); **Y10T 408/9098** (2015.01)

(58) **Field of Classification Search**

CPC ... B23B 51/0018; B23B 51/107; B23B 51/10;

B23B 2251/02; B23B 2260/0482; B23D 77/12; B23D 2277/02; Y10T 408/8925; Y10T 408/906; Y10T 408/9065; Y10T 408/907; Y10T 408/9098; Y10T 279/17846; Y10T 279/17863; Y10T 279/17957

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

129,414 A * 7/1872 Leet B25B 15/02 223/104
1,839,835 A * 1/1932 Cook B25B 23/0042 279/102
2,641,478 A * 6/1953 Sigg B25B 15/02 279/102
2,655,964 A * 10/1953 Labbee, Jr. B23B 49/005 408/224
4,123,193 A * 10/1978 Hill B23B 49/005 408/202
4,480,951 A * 11/1984 Regensburger F16B 25/0031 408/213
5,271,697 A * 12/1993 Johnson B23B 31/1071 279/75
6,120,225 A * 9/2000 Palm F16B 19/083 408/225

(Continued)

Primary Examiner — Eric A Gates

(57) **ABSTRACT**

A reamer includes a shank, a washer, a ring and a blade. The shank is a polygonal rod and includes an annular groove made in a periphery and a bore made in an end. The washer includes a slot. The ring includes a circular opening. The blade includes an insert inserted in the bore through the slot and the circular opening. The circular opening is made of a diameter larger than a width of the blade to allow the blade to rotate relative to the ring.

4 Claims, 7 Drawing Sheets

